

VeCOAX-T4

HD Multi-Video Distribution made EASY



Turn Four HD Videos into a real digital RF
and broadcast to all of your DVB-T TVs via the antenna coax cable

- ✓ *FOUR Simultaneous HDMI Video inputs – 4 HD Programs !*
- ✓ *DVB-T output for Antenna Coax distribution*
- ✓ *IPTV output for wifi distribution*
- ✓ *Full Local control via Display & Keyboard*
- ✓ *Also remote control via PC*
- ✓ *Lowest Cost per channel - Breakthrough Price !*



Enjoy TRUE FULL-HD Quality Everywhere



The VeCOAX T4 : convert FOUR HDMI HD Videos into DVB-T for broadcast over coax to unlimited standard HD TVs

Why VeCoax-T4 is the solution ?

VeCOAX-T4 is the perfect, final and affordable solution to distribute Quality Full-HD Multi-Video to unlimited standard HD Televisions without requiring any special adapter on each TV nor rewiring with new cables, but using the standard antenna coax cable.

Simple Distribution via the Antenna Cable

Based on the DVB-T Broadcasting technology, the VeCoax-T4 converts FOUR independent HDMI HD videos and stereo or surround sound into a real DVBT digital terrestrial frequency you can inject straight to the local antenna wall-mount socket, so all the TVs connected to the same coax cable will receive it as it would be just another FOUR standard DVB-T HD programs. Each HDMI input is independent and can operate at the same or different resolution from the others.

True HD Full-Quality on all your HD TVs

VeCOAX-T4 does not compromise with your quality of picture, thanks to its broadcast-grade processors that captures and distribute your Full-HD contents with almost no-delay and no flaws, perfect on Sports, High Motion Video, Text Crawls in Digital Signage, and any other content.

Multiple Programs

VeCOAX-T4 RF output can be set to any VHF or UHF channel, with selectable world-wide standards, coexisting with any other RF and channels already on the same Coax. Multiple units can be used to broadcast up to the wanted number of HDTV programs through the same Coax Cable to all your TVs.

Connects to any Video Source

VeCOAX-T4 is compatible to any BluRay Disk Player, DVD Player, Satellite and Cable HDTV set top box, DVI and HDMI computer output, USB Media Player, HD CCTV camera system, Home & Building Automations, and any other device with HD or SD digital or analog Audio/Video Outputs.

HDMI inputs makes this converter suitable for pro applications where perfectness of HD Picture Quality is most wanted.

Easy Setup and Control

VeCOAX-T4 can be totally controlled via the local Display and Keyboard without the need to connect a PC. Remote Control is also possible via the standard IP LAN network through the included management software.

At Galance


- ✓ **FOUR HDMI Full-HD Inputs**
- ✓ **DVB-T RF Output**
- ✓ **Also IPTV Output**
- ✓ **Control via LCD/Keyboard**
- ✓ **Also Remote Control via PC**
- ✓ **Desktop & Rack-Mount**
- ✓ **Cool & Silent operation**
- ✓ **Professional Connectors**
- ✓ **Perfect and Clean picture on High Motion Video, Sport, Text Crawls, etc.**
- ✓ **VHF/UHF world-standards compatible**
- ✓ **Multiple Channels on the same Coax**
- ✓ **Infrared Remote Control Repeater (option)**



Total Quality, Never been so simple



BLOCK DIAGRAM



Save on Cables & Adapters

VeCOAX-T4 does not need any additional set top box, nor adapters, extra cables and power supplies on each TV in every room, since it distributes your Full HD Video via the common antenna cable.

You'll be able to switch between your new HD channels and any other standard received channel just using the original TV remote control. Each room – just the TV – Clean, Easy, HD.


Home Entertainment

VeCOAX-T4 is the perfect HD Multi-Video distribution solution for any Home Entertainment system, connecting any Home-Video Master system to all the other TVs in each room without the need to duplicate the AV equipment. The IR option allows infrared remote control feedback from any room to the master AV system via the same Coax Cable.



Hotel TV

VeCOAX-T4 is the ideal choice to create unlimited HDTV channels in any Hotel and distribute to common TVs in every room via the Coax Cable. Digital Signage, Info Channels, Meeting channels, and any other video taken from any HD / SD Video source.



Sport Bars & Casinos

VeCOAX-T4 is the perfect solution for quality distribution to HDTV screens in Sport Bars, Restaurants, Casinos



And any other..

Campus, Schools, Hospitals, Cruise Liners, Boats, Stages, Airports, Metro, Corporates, and yours..

Benefits

- ✓ Save on new Cables & Distribution costs since it runs on the existing antenna coax cable
- ✓ Save on adapters on each TV since it does not need anything but the TV.
- ✓ Add as Many TVs you need by just connecting it to the antenna coax cable.
- ✓ FOUR HDMI inputs for the best Picture Quality and Lowest Cost Per Channel
- ✓ ASI input to feed programs from other ASI sources to the same DVBT RF out and IP streaming out
- ✓ Use more units to inject multiple HD Video to the coax cable, also from different rooms/injection points
- ✓ Use the original TV remote control – no need for any additional remote control

Compatible to Everything



Video Inputs

HDMI

- 4x HDMI 1.3 Full HD Input
36-bit color depth
1080i / 720P Resolutions
59,94 / 50 Frames/Fields
- HDMI Audio Stereo/Surround

Audio Inputs

HDMI

- 4x HDMI Audio Stereo/Surround

Video Encoders

Simultaneous HD Encoding

- FOUR independent / simultaneous encoders, Full Frame, Full Quality, Full Resolutions.
- Each Encoding channel can be set to the wanted parameters independently from the others

Video Encoding profiles per each channel

- Mpeg-4 H.264 AVC
- HD HP@L4 High Profile @ Lever 4.0
1920x1080i, 1280x720p
- RF Out follows the sum of the encoding settings

Compression Modes per each channel

- Broadcast-Quality Hierarchical motion estimation
- VBR Statistical Multiplexing
- Also CBR Mode
- 0.3 Mbps to 20 Mbps
- Programmable Low Delay
100 -400 msec
- Programmable GOP
- User defined Program Name, Service Provider, and other PSI information
- User defined PIDs

Audio Encoders

Simultaneous Audio Encoding

- FOUR independent / simultaneous audio encoders, one per each HDMI input

Audio Encoding profiles per each channel

- Mpeg-1 Layer II – All Modes
- AAC-LC AAC-HE (option)
- Surround pass-through

ASI input & Remuxing

ASI input

- 1x ASI Burst/Byte 188/204 Transport Stream Input
- Accepts any MPTS (multi program transport stream) or SPTS (single program transport stream)
- Rates up to 214 Mbit/s

Remultiplexing

- Decoding of the Services information from the ASI input
- Ability to “ REMUX “ selected DVB services (programs) from the ASI input to the ASI/IP/RF outputs, together with the FOUR generated New programs from the 4 HDMI in.
- Complete management of PIDs, Service provider/s, Service Names, manual or automatic PIDs remapping or pass-through, PCR correction, EMM/ECM cas and DSMCC PIDs and descriptors pass-through, etc.
- Full Remultiplexer features are completely controlled by using our NMS Software (included) on any PC

RF Modulator Out

Modulation Standard

- DVB-T Standard DVB ET300429
- HD Broadcast 1080i /720P
- SD Broadcast 576i / 480i
- Frequency range:
VHF 177.5-226.5 MHz
UHF 474 – 858 MHz
- Channel Bandwidth : 7/8 Mhz
- RF Out Level: Adjustable from 91dBuV to 61dBuV
- Impedance : 75 Ohm (50 opt.)
- MER: Professional-Grade >45 dB
- Spectrum Shoulders: 55 dB for perfect adjacent-channel operations
- Out Filter: -70 dB of Harmonic and spurious suppression
- DVB-T modulations: QPSK, 16QAM, 64QAM
- FFT: 2K / 8K mode
- Guard Intervals: 1/4, 1/8, 1/16, 1/32
- Code Rates: 1/2, 2/3, 3/4, 5/6, 7/8
- 2x ASI Monitoring Outputs

IPTV Out

IP Streaming out

- MPTS IP Streaming out
- Simultaneous to RF out
- Ideal for Wifi and Lan Simulcast
- UDP Multicast with full IGMP support
- Unicast up to 90 Mbit/s of requests.
- Complete config of network param.
- Compatible with any IP Set Top Box, Video player software, VLC, etc.

Control

Full Local Control/Setup

- Instant Access to all fetures from the local Keyboard and Large Display, without the need for a PC.

Pro Remote Control

- The system comes with a full-featured Network Management Software, to control unlimited units from remote PCs via common IP connection and SNMP protocol.

Physical and Power

Power - 90 to 240 VAC 50/60 Hz - 28 Watts

Cooling - Almost Cold and quiet operation
internal fan side to side flow

MTBF - 40,000 Hours 24/7 non-stop

Dimensions 490x455x44.5 millimeters
(19.2 x 17.9 x 1.75 inches)

Weight - 6,5 Kilograms (14,3 lbs)

Operating Temperature

-10°C to 50°C (14°F to 122°F)

Relative Operating Humidity

10% to 90% (Non-condensing)

Mounting - Rack Mount via provided brackets
Desktop via provided Rubber Feet

Compliance

EN55022, EN61000-3-210, EN61000-3-310,
EN55024, CISPR22, EN60950-1, IEC60950-1
UL60950-1, UL60065, FCC Class B
Warranty - 1 Year Standard / 3 yrs Extended

Ordering Information

VeCOAX-T4 World-Wide
VeCOAX-T4O OEM Version

